
Description

3/2 and 5/2 ways monostable solenoid valve to control pneumatic double and spring return actuators. Conversion from 3/2-way to 5/2-way valve simply by turning the seal.




Product features

	VSNC
• Orifice	7mm
• Nominal flow	1250 l/min
• Interface	NAMUR
• Pressure diff.	min. 2,5 bar, max. 8 bar
• Temperature range	-20°C ÷ 60°C

IA motion	Solenoid valve IP65
IA050-IA600	**VSNC-FC-M52-MD-G14-FN-1A1+G.24VDC**
	VSNC-FC-M52-MD-G14-FN-1AA1+G.24V/50-60Hz
	VSNC-FC-M52-MD-G14-FN-16BA1+G110V50-60Hz
	VSNC-FC-M52-MD-G14-FN-3AA1+G.230V50-60Hz
	Optionen: 12VDC, 48VDC
	Other versions on request

IA050 - IA250





IA300 - IA600




Dimensions

VSNC 3/2 + 5/2







B1	B2	B3	B4	D1	D2	H1	H2	H3	H4	H5	H6	L2	L4	L6	L7	L8	L9	L10	L11	L12	L13	L14	L15	[Watt]	[kg]
31.8	18.6	7.3	1.9	G¼	M5	49.9	28.2	32	7.8	4.4	57.2	162.2	161.1	127.8	53.8	24	34.4	33.3	90.3	65.8	41.3	53.8	24	3	0,42

InterApp

MEMBER OF THE AVK GROUP

Fluids under control.

Notes

InterApp AG
Grundstrasse 24
CH-6343 Rotkreuz
Phone +41 (0) 41 7982233
Fax +41 (0) 41 7982234
info@ch.interapp.net

InterApp Ges.m.b.H.
Kolpingstrasse 19
A-1230 Wien
Phone +43 (0) 1 6162371-0
Fax +43 (0) 1 6162371-99
info@at.interapp.net

InterApp Italiana
Via Gramsci 29
I-20016 Pero (MI)
Phone +39 02 339371
Fax +39 02 33937200
info@it.interapp.net

InterApp GmbH
Schillerstrasse 50
D-42489 Wülfrath
Phone +49(2058) 8909250
Fax +49(2058) 8909255
info@de.interapp.net

AVK Válvulas S.A.
InterApp Válvulas S.A.
Poligono Industrial Francoli, parcela 27
E-46006 Tarragona
Phone +34 977 543 008
Fax +34 977 541 622
avk@avkvalvulas.com

The technical data are noncommittal and do not assure you of any properties. Please refer to our general sales conditions. Modifications without notice.
© 2017 InterApp AG, all rights reserved